

NOTES:-

- 1. ALL UNDERGROUND ELECTRICAL SERVICE CONNECTIONS SHALL BE LAID IN ACCORDANCE WITH REQUIREMENTS OF ETSA UTILITIES AND THE AUSTRALIAN STANDARD SPECIFICATION AS 3000 PART 1 1976 (SAA WIRING RULES).
- 2. THE UNDER GROUND ELECTRICAL CONNECTION TO A PROPERTY SHALL ONLY BE UNDERTAKEN BY A SUITABLY QUALIFIED LICENSED CONTRACTOR.
- 3. TRENCHING AND BACKFILL SHALL BE DONE IN ACCORDANCE WITH THE CITY OF SALISBURY STANDARD DETAIL SHEET SD-33.
- 4. FOOTPATH PAVEMENTS SHALL BE REINSTATED IN ACCORDANCE WITH THE CITY OF SALISBURY STANDARD DETAIL SD-32,SD-37 AND SD-38.
- 5. ALL DISTURBED VERGE AREAS SHALL BE REINSTATED WITH "LIKE" MATERIAL.
- 6. REFER UNDERGROUND ELECTRICAL SERVICE CONNECTION.
- 7. SEWER CONNECTION TO BE MINIMUM OF 300mm FROM ELECTRICAL CONNECTION IN ACCORDANCE WITH AS3500.1:2003.

